

Via Staffora, 18/9 20090 Opera (Mi)- ITALY Tel. +39-02-57606750 Fax. +39-02-57606752 info@lumed.com www.lumed.com

EP-ES1530100 EUROsedeo 3500 handkrank ergometer







NB the product is subject to changes without prior notice.

Description

The recline safety ergometer EUROsedeo are state-of-the-art high performance ergometers.

The models designated can be equipped with an additional blood pressure measuring module. This module is situated in the ergometer's control console. The device meets the highest quality standards in precise physical exertion tests for conducting measurements in the field of cardiovascular and pulmonary function diagnostics. High safety standards are ensured thanks to the patient's reclined position.

The following characteristics make the unit exceptional:

- ✓ Intelligent design for a safe use
- ✓ Easy access supported by handlebars and sliding seat
- ✓ Robust and secure backrest
- ✓ Comfortable and stable, also for obese patients
- ✓ Easy adjustment of saddle and headrest
- ✓ Remote operation personalised programs training programs
- ✓ Performance range from 0-999 watts
- ✓ Very quiet drive unit
- ✓ Optional NIBP module
- ✓ Optional SpO2 module
- ✓ Optional SMART interface
- ✓ Optional Bluetooth interface for PC, Stress-Test or CPET systems etc
- ✓ Optional WLAN interface for PC, Stress-Test or CPET systems etc
- ✓ Optional chest ECG module
- ✓ Optional chest Hear-Rate meter



Via Staffora, 18/9 20090 Opera (Mi)- ITALY Tel. +39-02-57606750 Fax. +39-02-57606752 info@lumed.com www.lumed.com

| Technical data | |
|------------------|--|
| Workload: Brake: | ✓ Manual Mode: from 5 to 999 W, resolution 5W or 25 W ✓ Internal Computer: from 1 to 999 W, resolution 5W or 25 W ✓ External system: from 1 to 999 W, minimal res. 1 W ✓ Error: 3% or 3 W (range 20 - 800 W) electromagnetic, driven by microprocessor, independent from revolution-rate |
| | |
| Precision: | Torque control according to weight. |
| Display: | ✓ Graphic color LCD touch 57x43 mm, to show Hear-Rate, Workload, Time ✓ The head can rotate 180° ✓ A specific display shows just the revolution rate |
| Interface: | ✓ Manual programming (no automatic workload protocols are available) ✓ Built-in Computer ✓ Interface towards PC via RS232 (opto-isolated), protocols: ✓ Ergosana ✓ P10 ✓ P10E ✓ P1 ✓ P2 ✓ P10F |
| Ergonomy; | max patient weight 160 kg. Infinitely variable for heights from 120 to 210 cm. |
| Size & Weight; | base 150x83cm; weight 46 Kg approx |
| Power: | 230 VAC 50-60 Hz, 115 VAC 50-60Hz |